



Approval	 	
Capability	UL	IEC
Standard	600V	800V
Rated Voltage	85A	76A
Rated Current	12-4AWG	0.2-16mm ²
Wire size	12.2/42.5/1.5mm	54/61.5/59mm
T/W/End plate	8KV/3	
Height(mm)(NS35:7.5/NS35:15/NS32)	11mm	
Rated surge voltage/Contamination Class	M4/1.2N.m/10.5Lb-in	
Stripping length	B7	
Screw thread/Tightening torque	PA/V-0	
Internal cylindrical gage		
Insulating Material/Inflammability class		
Specification	Model	Pieces
(1) Terminal block	PC 16	50
(2) End cover	D-PC 16	50
(3) Fixed bridge		
2-P		
3-P		
5-P		
10-P	FBI 10-12	10
(4) Step bracket		
(5) Insertion bridge		
2-P		
3-P		
10-P	EB 10-12	10
(6) Isolator bridge bar, 10P		
(7) Bridge bar isolator		
(8) Switching bridge		
(9) Separating plate	TS-K	50
(10) Separating plate, width 1.5mm	ATP-PC	50
(11) Test plug socket	DSB 4/7/6	100
(12) Test plug socket, insulated	DSBJ 4/15/6	
(13) Zack strip	ZB10	

HOW TO ORDER :

- **P** - -

X	X	X
---	---	---

Customer Request

Series No.

No. of pole

Color

1	Gray	4	Green	7	Trans- parent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	white

 mm (INCH)	 DEGSON ELECTRONICS CO., LTD.
 THROUGHT LINE PROJECTION	NAME PC 16