



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 Contact Resistance: 10m Ω Max
 Insulation Resistance: 500M Ω Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
02P	2.50	8.00
03P	5.00	10.50
04P	7.50	13.00
05P	10.00	15.50
06P	12.50	18.00
07P	15.00	20.50
08P	17.50	23.00
09P	20.00	25.50
10P	22.50	28.00
11P	25.00	30.50
12P	27.50	33.00

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 HELEN DATE 制表日 2009/11/26	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE X. X \pm 0.25 X. XX \pm 0.15 X. XXX \pm 0.05 SIZE. 紙張尺寸 A4 REV. 版本 A	PART NAME 品名 2.5mm FEMALE HOUSING 1X??P W/LOCKING RIBS BLACK COLOR LOW-LEAD PART NO. 料號 H2325-XXPB0000R