



- NOTES :
- ENVIRONMENTAL : TEMPERATURE RANGE -20°C TO +85°C
  - ELECTRICAL :  
 RATED : 1.5A @ 40V AC (rms)  
 CONTACT RESISTANCE : 20 MILLIOHMS MAXIMUM  
 INSULATION RESISTANCE : 1000 MEGOHMS MINIMUM  
 DIELECTRIC WITHSTANDING VOLTAGE : 500V AC (rms)
  - MECHANICAL :  
 MATING FORCE : 10 LB. (4.5Kg) MAXIMUM  
 UNMATING FORCE : 2.2 LB. (1Kg) MINIMUM , 8.8LB. (4Kg) MAXIMUM
  - MATERIAL :  
 HOUSING : GLASS FILLED THERMOPLASTIC , WHITE, UL 94V-0  
 CONTACT : BRASS  
 SHELL : COLD ROLLED STEEL , NICKEL OVER COPPER PLATED  
 BOARD LOCK : ZINC ALLOY OR COPPER , TIN PLATE

玄茂科技股份有限公司  
 HSUAN MAO TECHNOLOGY CO., LTD.

UNIT		SCALE	PART NAME	
MM		2:1	DVI CONNECTOR-24P(FEMALE) STRAIGHT INTEGRATED	
APPD.	CKD.	TOLERANCE	PART NO.	REV.
		± 0.5	C0507-24FSXSW0	A

制表日: 2002/12/04

DRAWING. APPROVED

Jane