



**Specification:**

Contact Resistance: 30m Ohm Max.

Insulation Resistance: 1000M Ohm Min. At 500VDC.

Rated Voltage And Current: 1.5A At 250VAC Minimum.

Dielectric Withstanding Voltage: 750V AC (rms) for 1 Minute(Rev. 1.1)

Durability (Life Test): 1500 Cycles

Insertion Force: 35 Newton Maximum.

Extraction Force: 10 Newton Minimum.

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	WHITE	1	
2	TERMINAL	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	4	Gold:1~3u*; Ni:40~60u*; TIN:120u* (100% pure Tin of lead free plating)
3	SHELL	BRASS T:0.3	NICKEL PLATED	1	Ni: 80~120U"
4	BOTTOM COVER	PBT G.F.	WHITE	1	

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 Hedy DATE 制表日 2012/08/09	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	TOLERANCE 容許公差 X, Y ±0.38 XX ±0.25 XXX ±0.13 XXXX ±0.05 SIZE 紙張尺寸 A 4 REV. 版本 A	PART NAME 品名 USBUSB A TYPE DIP TYPE 4P FEMALE 180° NICKEL SHELL SELECTIVE GOLD PLATING WHITE COLOR ROHS A TYPE DIP TYPE 12P FEMALE 90° HORIZONTAL SELECTIVE GOLD PLATING BLACK COLOR ROHS PART NO. 料號 C8317-04AFSSW0R